

[54] **PRESENTATION DISPLAY APPARATUS  
FOR DISPLAYING TWO DIFFERENT  
IMAGES ON SEPARATE DISPLAYS FOR A  
LISTENER AND A SPEAKER**

[75] Inventors: Mitsuo Saito, Yokosuka; Tsukasa Matoba, Kawasaki; Toshio Okamoto, Tokyo, all of Japan

[73] Assignee: Kabushiki Kaisha Toshiba, Kawasaki, Japan

[21] Appl. No.: 81,747

[22] Filed: Aug. 5, 1987

[30] **Foreign Application Priority Data**

Aug. 15, 1986 [JP] Japan ..... 61-191254

[51] Int. Cl.<sup>4</sup> ..... G06F 15/626

[52] U.S. Cl. .... 364/521; 340/718;  
340/734

[58] Field of Search ..... 364/521, 518, 522;  
358/102, 185; 340/718, 732, 734, 705, 711, 701,  
703; 434/323

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

3,936,596	2/1976	Inuiya	358/102
3,971,000	7/1976	Cromwell	340/734 X
4,286,263	8/1981	Lindberg	340/718 X
4,333,152	6/1982	Best	358/102 X
4,712,191	12/1987	Penna	364/521 X
4,730,218	3/1988	Goodrich	358/102 X
4,758,887	7/1988	Engel et al.	358/185 X

Primary Examiner—A. D. Pellinen

Assistant Examiner—A. Jonathan Wysocki  
Attorney, Agent, or Firm—Oblon, Spivak, McClelland,  
Maier & Neustadt

[57] **ABSTRACT**

A presentation display apparatus including a data storage section for storing a plurality of explanative image data each having (R), (G) and (B) color image components, a data processing section for adding, to the explanative image data from the data storage section, function select image data different in color component from the explanative image data, an image memory for storing the image data of one screen image output from the data processing section, a listener's first display device for displaying the image data which is delivered from image memory and a speaker's second display device. The image data output from the image memory is supplied through a first color converter to the listener's display device and through a second color converter, the explanative image data is alone directly delivered as conversion image data in spite of function select menu image data, so that only the explanative (R)/(G)/(B) image is displayed on the listener's display device. In the second converter, the (R)/(G)/(B) input data are directly output as conversion image data when the function select image data is "0" and otherwise converted to all "1" when the function select menu image is "1" so that the function select menu and (R)/(G)/(B) explanative image are overlappingly displayed on the second display device.

16 Claims, 4 Drawing Sheets

